


COMMON S/IPX



REF	A6166A	Common S/IPX alu
	A6166W	Common S/IPX white
	A6166B	Common S/IPX black

LED	Xicato
LED LM OUTPUT	700 / 1.300 lm
POWER CONS.	according to lm output - see table p. 195
COLOR TEMP.	2.700 / 3.000 / 4.000 K
CRI	80 or +95
COLOR QUAL.	artist / beauty / vibrant / vibrant artist
REFLECTOR	40° / 60°
FINISH	anodised white RAL 9016 tex black RAL 9005 tex
ADJUSTABLE	n/a
CUT-OUT	Ø 80 mm
DRIVE CURRENT	supplied with driver
REMARK	with blade springs



MODEL	REFERENCE	LM OUTPUT	CRI / CCT	BEAM	DIMMING
COMMON S/IPX ALU COMMON S/IPX WHITE COMMON S/IPX BLACK	A6166A A6166W A6166B	700 lm	827 - 830 - 840 - V830	16°	ND PD A D
			927 - 930 - 940 - V930 - BT - F+		
	1.300 lm	827 - 830 - 840 - V830	40°		
		927 - 930 - 940 - V930 - BT - F+	60°		
				40° / 60°	

ND: non dimmable / PD: phase dimming / A: 1-10V / D: Dali