

# JACK SINGLE A-TRACK-TIF



## GENERAL INFO

JAF/C/9CT/R - Jack

JA2F/9CT/R – Jack<sup>2</sup>

ATJAF/9CT/R - Jack AT

AT2JAF/9CT/R - Jack 2 AT

ATLJAF/9CT/R - Jack AT LOW

ATL2JAF/9CT/R - Jack 2 AT LOW

F = Finish / C = ceiling base / CT = Color temp. / R = Reflector

Jack is available with O4, I4 and I6 ceiling base.

Jack<sup>2</sup> always needs a Jackpoint option to plug into.

With Jackpoint Stretch ceiling option there is no canopy visible when Jack<sup>2</sup> is plugged in.

## SPECIFICATIONS

**LED LM OUTPUT** 420 lm

**POWER CONS.** 4,2W

**DRIVE CURRENT** 48Vdc

**COLOR TEMP** 2700K / 3000K

**CRI/GAI** >90

**REFLECTOR** 16° - 25° - 48°

**FINISH** Black (BL) / White (WH) / Brushed Ano (BA) / Bronze (BR) / Gun Metal Bronze (GM) / Champagne (CH) / Canon Fusil (CF)

**REMARK** Options: C6004 – Jack Honeycomb option

only dali dimmable