



Jack – Jack² - Jack AT – Jack AT LOW

Ref.	JAF/C/9CT/R - Jack JA2F/9CT/R – Jack ² ATJAF/9CT/R - Jack AT AT2JAF/9CT/R - Jack 2 AT ATLJAF/9CT/R - Jack AT LOW ATL2JAF/9CT/R - Jack 2 AT LOW
	F = Finish / C = ceiling base / CT = Color temp. / R = Reflector

LED lm output	382 lm
Power	4,2 W – 48Vdc Dali on-board, hot-swappable
CRI - Color temp.	>90 - 2700K / 3000K
Finish	Black (BL) White (WH) Brushed Ano (BA) Bronze (BR) Gun Metal Bronze (GM) Champagne (CH) Canon Fusil (CF)
Reflector	10° - 25° - 40°
Dimensions	Ø25mm x 110mm
Options	C6001 – Jackpoint Trimless C6002 – Jackpoint Stretch ceiling C6003/W – Jackpoint Canopy White C6003/B – Jackpoint Canopy Black C6004 – Jack Honeycomb option

Jack is available with O4, I4 and I6 ceiling base.

Jack² always needs a Jackpoint option to plug into.

With Jackpoint Stretch ceiling option there is no canopy visible when Jack² is plugged in.